

# B215.2

С хвостовиком по ГОСТ 25827-93 исп.3  
Shank GOST 25827-93 vers.3

Код / Code	K	d <sub>max</sub>	D	A	Кг/kg
<b>B215.2.40.070.16ER</b>	40	10	28	70	1,00
<b>B215.2.40.100.16ER</b>	40	10	28	100	1,16
<b>B215.2.40.150.16ER</b>	40	10	28	150	1,52
<b>B215.2.50.090.16ER</b>	50	10	28	90	3,00
<b>B215.2.50.150.16ER</b>	50	10	28	150	3,50
<b>B215.2.40.070.25ER</b>	40	16	42	70	1,21
<b>B215.2.40.120.25ER</b>	40	16	42	120	1,67
<b>B215.2.50.090.25ER</b>	50	16	42	90	3,23
<b>B215.2.50.150.25ER</b>	50	16	42	150	3,80
<b>B215.2.40.050.32ER</b>	40	20	50	50	1,20
<b>B215.2.40.100.32ER</b>	40	20	50	100	1,70
<b>B215.2.50.085.32ER</b>	50	20	50	85	3,30
<b>B215.2.50.150.32ER</b>	50	20	50	150	3,90
<b>B215.2.50.070.40ER</b>	50	26	63	70	3,20

